
TECHNICAL DATA SHEET

STYLEARTSTONE

STYLEARTSTONE®

PRODUCT DESCRIPTION

STYLE ART STONE is a rapid setting acrylic polymer modified cement based composite. It is a shrinkage-compensated material of low permeability and is durable in all conditions of external weathering. The compound is alkali free and as such is free from the efflorescence associated with ordinary cement based systems. The product contains a fine decorative aggregate and powder pigments upon request, carefully controlled to give a consistent decorative surface finish after treatment with a proprietary sand blasting or acid etch.

SPECIFICATIONS

Wet density 1950 kg/m³ (avarage)
Dry density 1850 kg/m³ (avarage)

APPLICATION AREAS

Glass reinforced or non glass reinforced decorative architectural mouldings, and castings. Glass reinforcements scan be utilised for lightweight, high impact panels. It can also be used to create garden ornaments and statuary, and is suitable for water-features.

KEY ATTRIBUTES

Improved flexural strength and stability
Excellent abrasion resistance and impact strength
High compressive and tensile strength
Rapid curing and high early strength gain
Shrinkage compensated and dimensionally stable
Resistant to high temperature, sulphate and winter conditions

STYLEARTSTONE® is a Registered Trademark

The above information and recommendations are based upon our experience and are offered merely for advice. They are offered in good faith but without guarantee, as conditions and methods of use are beyond our control. It remains the responsibility of the end user to determine the suitability of the materials for the particular purpose intended

CONTACT

Fener Kalamış Cad. Körfez Apt. A Blok No:17/2 Kalamış Kadıköy / İstanbul / TURKEY
Mobile: +90 (541) 246 30 82
Phone: +90 (216) 414 90 11-12
Fax: +90 (216) 414 30 76
info@styleartstone.com